



Temporary Power Distribution

TECHNICAL DATA SHEET

MD10



A 125A three-phase (400V) power distribution box designed to distribute temporary power from one area to another. The 125A 3 phase plug and play distribution board is easy to relocate across site and blends in well with the surrounding environment.

TECHNICAL DATA

Incomer	Outgoing	Dimensions	Weight
125A 400V 3P+N+E IP67 Appliance Inlet. Protection: 125A 4 Pole MCCB	<p>> 3 x 63A 400V 3P+N+E IP67 Pnl Mnt Skt. Protection: 3 x 63A 4 Pole C-Type 100mA MCB + 4 Pole 100mA RCD</p> <p>> 3 x 63A 230V 1P+N+E IP67 Pnl Mnt Skt. Protection: 3 x 63A 2 Pole C-Type 100mA MCB + 2 Pole 100mA RCD</p> <p>> 3 x 32A 230V 1P+N+E IP44 Pnl Mnt Skt. Protection: 3 x 32A 2 Pole 30mA RCBO</p> <p>> 3 x 16A 230V 1P+N+E IP44 Pnl Mnt Skt. Protection: 3 x 16A 2 Pole 30mA RCBO</p>	H600 x W550 x D495 (mm)	45kg

WARRANTY AND CERTIFICATION

All temporary power distribution equipment supplied is manufactured by IDE in the UK and is rigorously tested to BS 7671 standards, with 12-month certification provided as standard.

Our distribution systems are built using components that conform to the following international standards:

- > EN 60309 – Plugs, socket-outlets, and couplers for industrial purposes
- > EN 60529 – Degrees of protection provided by enclosures (IP code)
- > EN 60947 – Low-voltage switchgear and controlgear

All components and assemblies are covered by a 24-month manufacturer's warranty, ensuring reliability, safety, and regulatory compliance throughout the deployment period.





Temporary Power Distribution

TECHNICAL DATA SHEET

MD10



PRODUCT FEATURES

- ✓ All switchgear and Tri-rated wiring are housed within a purpose-built polyethylene enclosure.
- ✓ Recessed socket and switchgear panels provide mechanical protection.
- ✓ Transparent windows allow:
 - Visual identification of switchgear status
 - Access in the event of a trip
- ✓ Inlet supply includes a phase rotation monitor.
- ✓ Each outlet features a red 'Power On' neon indicator.
- ✓ External brass earth stud for grounding.
- ✓ Enclosure material:
 - Black, 10mm thick, 300-grade high-density polyethylene (HDPE)
 - Good impact and chemical resistance
 - High rigidity
 - Density: 0.96 g/cm³
 - Moisture absorption: < 0.01%
 - Service temperature: -50°C to +80°C
 - Surface resistance: > 10¹⁴ ohms
 - IK09 impact resistance rating

T: 01543 574 111

E: enquiries@idesystems.co.uk

www.idesystems.co.uk